

Material Safety Data Sheet
according to Regulation (EU) N° 1272/2008

Cod.
Rev.01
Pag. 1 di
10

GG_003
September 2022

KrioNext® R410A

Section 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : R410A – Krioxnext R410A
SDS No. : GG_003
Registration-No. : 000000009881
Product Use Description : Refrigerant

1.3 Details of the supplier of the safety data sheet

Company identification : General Gas (Zhejiang) CO., LTD
Room 1802, West Tower, No. 1001, Jiangxi Road, Shangyu District, Shaoxing, Zhejiang, 312399
Phone ☎ 008613685862252
E-Mail ✉ carter.gu@generalgas-krioxnext.com

Section 2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Form : Liquefied gas
Color : Colourless
Odor : Weak

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas Simple Asphyxiant

2.2 GHS Label elements, including precautionary statements

Symbol(s) :



Signal word (CLP) :

Warning

Hazard statements (CLP) :

Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements (CLP) :

Storage:

Protect from sunlight. Store in a well-ventilated place.
May cause cardiac arrhythmia. May cause frostbite. May cause eye and skin irritation.

2.3 Carcinogenicity

: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

Section 3 Composition/information on ingredients

3.1 Chemical nature : Mixture

GENERAL GAS (ZHEJIANG) CO., LTD

📍 Room 1802, West Tower, No.1001, Jiangxi Road, Shangyu District, Shaoxing, Zhejiang, 312399
info@generalgas-krioxnext.com

A subsidiary of:

GeneralGas s.r.l.
Via Aosta, 5 – 20163
Cernusco sul Naviglio – Milan (Italy)

www.generalgas.eu/krioxnext

Material Safety Data Sheet
 according to Regulation (EU) N° 1272/2008

Cod.
 Rev.01
 Pag. 2 di
 10

GG_003
 September 2022

KrioNext® R410A

Section 4 First aid measures

4.1 Description of first aid measures

- Inhalation** : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact** : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion** : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

4.3 Indication of any immediate medical attention and special treatment needed

- : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frostbitten areas as needed.

Section 5 Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : The product is not flammable.
 Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting** : This product is not flammable at ambient temperatures and atmospheric pressure. However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
 Container may rupture on heating.
 Cool closed containers exposed to fire with water spray.
 Do not allow run-off from fire fighting to enter drains or water courses.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 Fire may cause evolution of:
 Halogenated compounds Hydrogen fluoride Carbon oxides
 Carbonyl halides

Material Safety Data Sheet
 according to Regulation (EU) N° 1272/2008

Cod.
 Rev.01
Pag. 3 di
10

GG_003
 September 2022

KrioNext® R410A

5.2 Special protective equipment for firefighters

: : In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit. No unprotected exposed skin areas.

Section 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away.
 Remove all sources of ignition.
 Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area.
 After release, disperses into the air.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 Avoid accumulation of vapours in low areas.
 Unprotected personnel should not return until air has been tested and determined safe.
 Ensure that the oxygen content is $\geq 19.5\%$.

6.2 Environmental precautions

: Prevent further leakage or spillage if safe to do so.
 The product evaporates readily.

6.3 Methods and material for containment and cleaning up

: Ventilate the area.

Section 7 Handling and storage

7.1 Precautions for safe handling

Safe use of the product

: Handle with care.
 Avoid inhalation of vapour or mist.
 Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.
 Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
 Follow all standard safety precautions for handling and use of compressed gas cylinders. Use authorized cylinders only.
 Protect cylinders from physical damage.
 Do not puncture or drop cylinders, expose them to open flame or excessive heat.
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
 Do not remove screw cap until immediately ready for use. Always replace cap after use.
 Advice on protection against fire and explosion : The product is not flammable.
 Can form a combustible mixture with air at pressures above atmospheric pressure.

7.2 Conditions for safe storage, including any incompatibilities

: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Storage rooms must be properly ventilated.

Material Safety Data Sheet
 according to Regulation (EU) N° 1272/2008

Cod.
 Rev.01
Pag. 4 di
10

GG_003
 September 2022

KrioNext® R410A

Ensure adequate ventilation, especially in confined areas. Protect cylinders from physical damage. Store away from incompatible substances.

Section 8 Exposure controls/personal protection

- 8.1 Protective measures** : Do not breathe vapour.
 Do not get in eyes, on skin, or on clothing.
 Ensure that eyewash stations and safety showers are close to the workstation location.
- 8.1.1 Engineering measures** : General room ventilation is adequate for storage and handling.
 Perform filling operations only at stations with exhaust ventilation facilities.
- Eye/face protection : Wear as appropriate:
 Safety glasses with side-shields
 If splashes are likely to occur, wear:
 Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves
 In case of contact through splashing: Protective gloves
 Neoprene gloves
 Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
 Wear cold insulating gloves/ face shield/ eye protection.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
 Wear a positive-pressure supplied-air respirator.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 For rescue and maintenance work in storage tanks use self- contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safet practice.
 Ensure adequate ventilation, especially in confined areas. Do not get in eyes, on skin, or on clothing.
 Remove and wash contaminated clothing before re-use. Keep working clothes separately.

Section 9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties**
- Physical state : Liquefied gas
- Colour : Colourless.
- Odour : Weak
- Odor threshold : Note: no data available
- pH : Note: neutral
- Freezing point : Note: no data available
- Boiling point/boiling range : -48.5 °C
- Flash point : Note: Not applicable
- Upper explosive limit : Note: None
- Evaporation rate : > 1

Material Safety Data Sheet
 according to Regulation (EU) N° 1272/2008

Cod.
 Rev.01
 Pag. 5 di
 10

GG_003
 September 2022

KrioNext® R410A

	Method: Compared to CCl4.
Lower flammable limit	: Note: None
Upper flammable limit	: Note: None
Vapor pressure	: 14,844 hPa at 21.1 °C(70.0 °F) 33,798 hPa at 54.4 °C(129.9 °F)
Vapor density	: 3 Note: (Air = 1.0)
Density	: 1.08 g/cm3 at 21.1 °C
Water solubility	: Note: no data available
Partition coefficient: n-	log Pow: 1.48

9.2 Other information

octanol/water	: Test substance: Ethane, pentafluoro- (HFC-125)
Ignition temperature	: > 750 °C
Decomposition temperature	: > 250 °C

Section 10 Stability and reactivity

10.2	Chemical stability	: Stable under normal conditions.
10.3	Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
10.4	Conditions to avoid	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
10.5	Incompatible materials	: Finely divided aluminium – Potassium – Calcium – Powdered metlas – Aluminium – Magnesium – Zinc.
10.6	Hazardous decomposition products	: Halogenated compounds - Hydrogen fluoride - Carbonyl halides Carbon oxides

Section 11 Toxicological information

11.1 Information on toxicological effects

Acute inhalation toxicity Pentafluoroethane	> 769000 ppm Exposure time: 4 h Species: Rat
Difluoromethane	LC50: > 520000 ppm Exposure time: 4 h Species: Rat
Sensitisation Pentafluoroethane	Cardiac sensitization Species: dogs Note: No-observed-effect level 75 000 ppm

Material Safety Data Sheet
according to Regulation (EU) N° 1272/2008

Cod.
Rev.01
Pag. 6 di
10

GG_003
September 2022

KrioNext® R410A

Lowest observed effect level
100 000 ppm

Difluoromethane

Cardiac sensitization
Species: dogs
Note: No-observed-effect level
>350 000 ppm

Repeated dose toxicity
Pentafluoroethane

Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOEL: 50000 ppm
Subchronic toxicity

Difluoromethane

Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 50000 ppm
Subchronic toxicity

Genotoxicity in vitro
Pentafluoroethane

Test Method: Ames test
Result: negative

Difluoromethane

Test Method: Ames test
Result: negative

Cell type: Human lymphocytes
Result: negative

Cell type: Chinese Hamster Ovary Cells
Result: negative

Cell type: Human lymphocytes
Result: negative
Method: Mutagenicity (in vitro mammalian cytogenetic test)

Test Method: Chromosome aberration test in vitro
Result: negative

Material Safety Data Sheet according to Regulation (EU) N° 1272/2008	Cod. Rev.01 Pag. 7 di 10	GG_003 September 2022
--	-----------------------------------	--------------------------

KrioNext® R410A

Genotoxicity in vivo
 Difluoromethane

Species: Mouse
 Cell type: Bone marrow
 Method: Mutagenicity (micronucleus test)
 Result: negative

Teratogenicity
 Pentafluoroethane

Species: Rat
 Application Route: Inhalation exposure
 NOAEL, Teratog: 50,000 ppm
 NOAEL, Maternal: 50,000 ppm
 Note: Did not show teratogenic effects in animal experiments.

Species: Rat
 Application Route: Inhalation exposure
 NOAEL, Teratog: 50,000 ppm
 NOAEL, Maternal: 50,000 ppm
 Note: Did not show teratogenic effects in animal experiments.

Difluoromethane

Species: Rat
 Dose: NOEL - 50,000 ppm
 Note: Did not show teratogenic effects in animal experiments.

Species: Rabbit
 Dose: NOEL - 50,000 ppm
 Note: Did not show teratogenic effects in animal experiments.

Further information

: Acute toxicity Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. May cause cardiac arrhythmia.

Section 12 Ecological information

12.1 Biodegradability

Pentafluoroethane

: Result: Not readily biodegradable.
 Value: 5 %
 Method: OECD 301 D

12.2 Further information on ecology

Additional ecological information

: This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.
 This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

Section 13 Disposal considerations

GENERAL GAS (ZHEJIANG) CO., LTD

Room 1802, West Tower, No.1001, Jiangxi Road,
 Shangyu District, Shaoxing, Zhejiang, 312399
info@generalgas-krypton.com

A subsidiary of:

GeneralGas s.r.l.
 Via Aosta, 5 – 20163
 Cernusco sul Naviglio – Milan (Italy)

www.generalgas.eu/krypton

Material Safety Data Sheet
 according to Regulation (EU) N° 1272/2008

Cod.
 Rev.01
Pag. 8 di
 10

GG_003
 September 2022

KrioNext® R410A

- 13.1 Disposal methods** : Observe all Federal, State, and Local Environmental regulations.
- Note** : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

Section 14 Transport information

- 14.1 DOT**
- UN/ID No. : UN 3163
- Proper shipping name : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, Difluoromethane)
- Class : 2.2
- Packing group : 2.2
- Hazard Labels : 2.2
- 14.2 IATA**
- UN/ID No. : UN 3163
- Description of the goods : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, Difluoromethane)
- Class : 2.2
- Hazard Labels : 2.2
- Packing instruction (cargo aircraft) : 200
- Packing instruction (passenger aircraft) : 200
- 14.4 IMDG**
- UN/ID No. : UN 3163
- Description of the goods : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, Difluoromethane)
- Class : 2.2
- Hazard Labels : 2.2
- EmS Number : F-C, S-V
- Marine pollutant : no

Section 15 Regulatory information

- 15.1 Inventories**
- US. Toxic Substances Control Act : On TSCA Inventory
- Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL
- Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory
- Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Material Safety Data Sheet
according to Regulation (EU) N° 1272/2008

Cod.
Rev.01
Pag. 9 di
10

GG_003
September 2022

KrioNext® R410A

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act

On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances

On the inventory, or in compliance with the inventory

NZIOC - New Zealand

On the inventory, or in compliance with the inventory

15.2 : A CSA does not need to be carried out for this product.

National regulatory information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard
Sudden Release of Pressure Hazard

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

New Jersey RTK

75-10-5

Section 16 Other information

	HMIS III	NFPA
Health hazard	1	2
Flammability	1	1
Physical Hazard	0	
Instability		0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

This Safety Data Sheet has been compiled in accordance with the applicable European Directives and is applicable to all countries that have translated the Directives within their national legislation.

The information contained in this sheet is based on the knowledge available to us at the date of the last version. The user must ensure the suitability and completeness of the information in relation to the specific use of the product. You should not interpret this document as a guarantee for any specific property of the product. Because the use of the product does not fall under our direct control, it is the user's duty

Material Safety Data Sheet
according to Regulation (EU) N° 1272/2008

Cod.
Rev.01
Pag. 10 di
10

GG_003
September 2022

KrioNext[®] R410A

to observe the laws and regulations in force regarding hygiene and safety under its own responsibility. They are not responsible for improper use.

End of Document